

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor, under Group #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6652)

Set post corner Tps. 29 and 30 S., Rs. 1 and 2 W., from which
 A Pine 30" dia., bears S.8°W., 37 lks.
 An Oak 18" dia., bears N.70°W., 56 lks.
 An Oak 18" dia., bears N.8°E., 72 lks.
 An Oak 12" dia, bears S.89°E., 180 lks.

GLO resurvey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6071)

At the Corner of Tps. 29 and 30 S. Rs. 1 and 2 W. which is partly obliterated. The old cor. which was a post has disappeared and the Pine described as bearing tree in sec. 1 has fallen and decayed. The other bearing trees are standing but the marks are deeply overgrown.
 I destroyed the old marks and re-establish the cor. in its original position as follows:
 Set a basalt stone 18x12x6 ins., 12" in the ground for cor. marked with 6 notches on each edge, from which
 A B.Oak 24" dia., bears N.2°E., 83 lks. dist., marked T29S R1W S31 BT.
 A Red Fir 10" dia., bears S.12°E., 20 lks. dist., marked T30S R1W S6 BT.
 A Red Fir 8" dia., bears S.39°W., 51 lks. dist., marked T30S R2W S1 BT.
 A B.Oak 24" dia., bears N.73°W., 57 lks. dist., marked T29S R2W S36 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6205)

The Cor. which is a basalt stone 18x12x6", firmly set in the ground, marked and witnessed as described by the surveyor general. I perpetuate this cor as follows: alongside the old cor.
 Set an iron post 3 ft. long, 3" dia., 24" in the ground for cor. of Tps. 29 and 30 S., Rs. 1 and 2 W., with brass cap marked:

	T29S	
	R2W	R1W
	S36	S31
	S1	S6
	T30S	
	1917	

from which
 A B.Oak 24" dia., bears N.2°E., 83 lks. dist. mkd. T29S R1W S31 BT. (Old BT) (Cont. Next Page)

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (SW. Tsp. cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Red Fir 10" dia., bears S.12°E., 20 lks. dist. mkd. T30S
R1W S6 BT (Old BT)
A Red Fir 8" dia., bears S.39°W., 51 lks. dist., mkd. T30S
R2W S1 BT. (Old BT)
A B.Oak 24" dia., bears N.73°W., 57 lks. dist. mkd. T29S
R2W S36 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, & crew - Jan.
15, 1968 - C.S. File 54/59-30

Found - 1917 GLO brass cap.
Orig. 30" Pine, now down and burnt, S.8°W., 24.4 ft.
Orig. 18" Oak, now rotted out, N.70°W., 37.0 ft.
Orig. 18" Oak now stob, N.8°E., 47.5 ft.
Orig. 12" now 17" Oak, S.89°E., 118.8 ft., opened
for scribe "BT". Fell this tree as very rotten
and would be a hazard.
New BTs- 16" D.Fir N.44°W., 26.8 ft. mkd. T29S R1W S31 CS BT
15" D.Fir N.73°E., 17.5 ft. mkd. T29S R1W S31 CS BT
Reblazed and rescribed 1904 BTs:
16" D.Fir S.9°E., (Rec. S.12°E.) 13.0 ft. mkd. T30S
R1W S6 CS BT.
10" D.Fir S.41°W., (Rec. S.39°W.) 33.0 ft. mkd. T30S
R2W S1 CS BT.

BLM resurvey by Donovan C. Harris, Cadastral Surveyor, under
Group #748, surveyed August 3-5, 1971 - (DCSO records Vol. 35
Page(s) 14584-85)

The cor. of secs. 1, 6, 31 and 36, remonumented by Fred
Mensch in 1905, subsequently remonumented by Strickler in
1917, with an iron pipe 3" dia., firmly set, extending 14"
above ground with brass cap mkd. in 1917
from which the remaining original bearing trees, recovered
and reblazed by Mensch
An Oak snag 21" dia., bears N.6°E., 75 lks. dist. mkd.
with rotted blaze. (Rec. N.2°E., 83 lks.)
An Oak snag 28" dia., bears N.71°W., 57 lks. dist. mkd.
with rotted blaze. (Rec. N.73°W.)
and bearing trees mkd. by Mensch
A Fir 17" dia., bears S.09°E., 19 lks. dist. with
illegible scribe marks visible on partly healed blaze.
(Rec. S.12°E., 20 lks.)
A Fir 10" dia. bears S.39°W., 51 lks dist with illegible
scribe marks visible on partly healed blaze.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (SW. Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and bearing trees mkd. by Powell in 1967
A Fir 17" dia bears N.72½°E., 25 lks dist with illegible scribe marks visible on partly healed blaze.
A Fir 16" dia. bears N.46°W., 41 lks dist with illegible scribe marks visible on partly healed blaze.

Survey by Glenn Baughman - For: U.S. Forest Service - July 1979 - C.S. File 58/176-35

Found 1" Iron pipe, 10" above the ground with a 2½" brass cap mkd. "T29S R2W R1W S36 S31 S6 S1 T30S 1917", from which
A 22" Oak bears N.70°W., 37.0 ft.
An 18" Oak stob bears N.8°E., 47.5 ft.
An 18" Oak stump bears S.89°E., 118.8 ft.
An 18"D.Fir bears N.44°W., 26.8 ft.
A 16" D.Fir bears N.73°E., 17.5 ft.
An 18" D.Fir bears S.9°E., 13.0 ft.
A 12" D.Fir bears S.41°W., 33.0 ft.
New BT - 10" D.Fir bears S.25°E., 38.4 ft., I marked "T30S R1W S6 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

Fd. OK, Sept. 1993 by H. Pieske - M 117-62

John Ransom, LS, USFS - Lance Goucher, Survey Tech - 5/2011 - C.S. File 65/80-50

Found - 4" brass cap on a 3" iron pipe projecting above ground in good condition.
A 18" fir brs. N.44°W., 26.8 ft. with a HB
A 17" fir snag brs. N.73°E., 17.5 ft. with a HDB
A 12" fir brs. S.20°E., 38.4 ft. With a HDB (record S.25°E)
A 15" fir brs. S.41°W., 33.0 fr with a HDB
A rotten fir stump, size indeterminate brs. S.10½°E., 13.0 ft. T30SR1WS6 visible on open face, scribing visible on partially visible older face (record S.09°E.)
Corner lies on a gentle west slope approximately 250 ft. South of the end of road 2810-310.
New - Painted BTs, nailed signs and tags and cleared brush around corner.
A 15" fir brs N.25°E., 23.9 ft. mkd T29SR1WS31BT on a double blaze with a washer stamped LS2561 on the lower face.