

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 31 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6072)

-----

Set a basalt stone 18x10x4 ins., 12" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Red Fir 18" dia., bears N.28°E., 102 lks. dist. mkd. ¼ S31 BT.

A Sugar Pine 40" dia., bears N.61°W., 74 lks. dist. mkd. ¼ S36 BT.

---

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6205-06)

-----

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to Sec. 31, T29S R1W only by destroying all markings referring to sec. 36 and marking ¼ on E. face. From cor.

A Red Fir 36" dia., bears East 75 lks. dist. mkd. ¼ S31 BT. (New BT)

A Red Fir 20" dia., bears N.28°E., 102 lks. dist., mkd. ¼ S31 BT. (Old BT)

---

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 25, 1969 - C.S. File 54/82-32

-----

Found - 20" D.Fir now 25", N.28°E., 67.3 ft. Scribe visible "¼ S31 BT"

36" D.Fir now 40", East 49.5 ft. Scribe visible "¼ S31 BT"

No trace of corner stone.

Set Brass cap at cor. mkd: County Surveyors Office

T	29	S
R	¼	R
2	S31	1
W		
1969		

New BTs- 8" D.Fir N.23½°E., 7.0 ft. scribed ¼ S31 CS BT.

6" D.Fir S.42°E., 3.9 ft. scribed ¼ S31 CS BT.

This corner lies 23.8 ft. South of ¼ cor. S36.

---

Fd. and used in BLM resurvey by Donovan C. Harris, Cadastral Surveyor, under Group #748, surveyed Aug. 3-5, 1971 - (DCSO records Vol. 35 Page(s) 14585-86)