

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only, (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6072)

-----  
Set a basalt stone 15x10x6 ins., 10" in the ground for cor. of secs. 25, 30, 31 and 36, marked with 5 notches on N. and 1 notch on S. edge, from which  
A Red Fir 16" dia., bears N.80°E., 70 lks. dist., mkd. T29S R1W S30 BT.  
A Red Fir 12" dia., bears S.66°E., 56 lks. dist., mkd. T29S R1W S31 BT.  
A Red Fir 12" dia., bears S.8°W., 59 lks. dist., mkd. T29S R2W S36 BT.  
A Laurel 6" dia., bears N.17°W., 55 lks. dist., mkd. T29S R2W S25 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6206)

-----  
Intersect the cor. of secs. 25, 30, 31 and 36, which is a basalt stone firmly set, mkd. and witnessed as described by the surveyor general. I change this cor. to refer to secs. 30 and 31, T29S R1W. only by destroying the marks on bearing trees referring to secs. 25 and 36.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 24, 1969 - C.S. File 54/82-31

-----  
Found - A 15x10x6 in. basalt corner stone, properly mkd.  
16" R.Fir now 28", N.80°E., 46.2 ft. Has open face and scribe of "W, S, 3".  
12" R.Fir now 20", S.66°E., 39.6 ft. Has open face, shows scribe of "T29S R2W S31 BT"

Place yellow tags on both bearing trees.  
Set brass cap in place of corner stone, mkd: County Surveyors Office 1969

T 29 S  
R S 36 | S30 R  
W | S31 W

Place corner stone by brass cap.  
This sec. cor. lies South 18.5 ft. from sec. cor. 25 & 36 only, T29-2.

Fd. and used in BLM resurvey by Donovan C. Harris, Cadastral Surveyor, under Group #748, surveyed Aug. 3-5, 1971 - (DCSO records Vol. 35 Page(s) 14587)