

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6073)

Set a basalt stone 20x6x6 ins., 15" in the ground for ¼ sec. cor. marked ¼ on W. face, from which

 A Sugar Pine 10" dia., N.45°E., 30 lks. dist., mkd. ¼ S30 BT.

 A Red Fir 16" dia., bears S.21°W., 46 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6207)

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 30, T29S R1W only, by destroying all marks referring to sec. 25 and marking ¼ on E. face. From cor.

 A Pine 10" dia., bears N.45°E., 30 lks. dist. mkd. ¼ S30 BT. (Old BT)

 A Fir 6" dia., bears S.41°45'E., 31 lks. dist., mkd. ¼ S30 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 24, 1969 - C.S. File 54/82-29

Found - 10" S.Pine now 16", N.45°E., 19.8 ft. Shows good scar and is good for bearing and dist.

 6" R.Fir now 10", S.42°E., 25.5 ft. Shows good scar.

 No trace of basalt stone.

Place yellow tags on both trees.

Set brass cap from BTs mkd: County Surveyors Office

T	29	S
R		R
2		¼
W		S30 W
		1969

This ¼ cor. lies South 33.7 ft. from ¼ S25 for T29-2.
Corner lies on steep West slope.