

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 100401

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6209)

Set a basalt stone 18x12x8 ins., 12" in the ground for cor. of secs. 13 and 24, marked with 3 notches on N. and S. edges, from which

A Fir 14" dia., bears S.54°W., 115 lks. dist. mkd. T29S R2W S24 BT.

No other bearing tree available; raise a mound of stone 2 ft. base 1½ ft. high W. of cor.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - July 30, 1969 - C.S. File 54/82-39

Found - 14" D.Fir now 29", S.54°W., 75.9 ft. shows good scar 18x12x8 in. stone at sec. cor., 3 notches on N. and S. edges.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S	
R <u>S 13</u> S18 R	
2 S 24 1	
W 1969 W	

New BTs- 10" D.Fir N.51°W., 41.7 ft. scribed T29S R2W S13 CS BT.

Old BT OK and tagged.

This cor. lies 17.8 ft. North of Cor. for 18 & 19, T29-1