

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6075)

Set a basalt stone 12x8x6 ins., 8" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which
A Red Fir 16" dia., bears N.86°E., 59 lks. dist. mkd. 1/4 S18 BT.
A Red Fir 20" dia., bears S.73°W., 178 lks. dist. mkd. 1/4 S13 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6209-10)

Intersect the 1/4 sec. cor. which is a basalt stone firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 18, T29S R1W only by destroying all marks referring to sec. 13 and marking 1/4 on E. face, from cor.,
A Fir 16" dia., bears N.86°E., 59 lks. dist. mkd. 1/4 S18 BT (Old BT)
A Fir 10" dia., bears S.64°30'E., 26 lks. dist. mkd. 1/4 S18 BT (New BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - May 1, 1969 - C.S. File 54/82-43

Found - 16" D.Fir now 22", N.86°E., 38.9 ft., shows good scar.
10" R.Fir now 17", S.64 1/2°E., 17.2 ft., shows good scar.
12x8x6 stone mkd. 1/4 W. face at 1/4 cor.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S
R 1/4 R
2 1
W | S18 W
1969

All BTs OK and tagged.
This cor. lies 13.2 ft. So of 1/4 cor. for sec. 13 only, T29-2