

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 100441

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 13 only, T29-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6210)

-----  
Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 cor. of sec. 13 only, with brass cap mkd. 1/4

S13 |  
1917

from which

A Fir 10" dia., bears S.74°30'W., 131 lks. dist. mkd. 1/4 S13 BT.

A Fir 10" dia., bears N.80°W., 70 lks. dist. mkd. 1/4 S13 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - May 1, 1969 - C.S. File 54/82-44

-----  
Found - 10" D.Fir now 29", S.74½°W., 44.5 ft. (Rec. 86.5)  
10" D.Fir now 34", N.80°W., 46.2 ft., shows faint scar.

Brass cap at 1/4 cor. properly mkd. S13 | 1917.

Reblazed and rescribed:

34" d.Fir N.80°W., 46.2 ft. scribed 1/4 S13 CSBT.

This cor. lies 13.2 ft. North of 1/4 cor. for S18, T29-1