

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, (West)

|            |                  |
|------------|------------------|
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6075)

-----

Set a porphyry stone 18x9x6 ins., 12" in the ground for cor. of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edge, from which

- A W.Fir 8" dia., bears N.70°E., 29 lks. dist. mkd. T29S R1W S7 BT.
- A Hemlock 8" dia., bears S.43°E., 14 lks. dist. mkd. T29S R1W S18 BT.
- A Hemlock 10" dia., bears S.65°W., 8 lks. dist. mkd. T29S R2W S13 BT.
- A Red Fir 36" dia., bears N.32°W., 59 lks. dist. mkd. T29S R2W S12 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6211)

-----

Intersect the cor. of secs. 7, 12, 13 and 18, which is a porphyry stone firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 7 and 18, T29S R1W only by destroying all marks referring to secs. 12 and 13.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April/May 1969 - C.S. File 54/82-42

-----

Found - 8" W.Fir now 13", N.70°E., 19.1 ft. shows good scar  
8" Hemlock now snag, S.43°E., 9.2 ft. scribe visible  
"29S R1W S18 BT".

18x9x6 stone at sec. cor. mkd. 2 notches on N. edge and 4 notches on the S.

Set Brass cap at cor. mkd: County Surveyors Office

|   |     |   |      |   |
|---|-----|---|------|---|
| T | 29  | S |      |   |
| R |     |   | R    |   |
| 2 | S12 |   | S 7  | 1 |
| W |     |   | S18  | W |
|   |     |   | 1969 |   |

New BT - 13" Hemlock S.66°E., 24.9 ft. scribed T29S R1W S18 CS BT.

This cor. lies 7.9 ft. North of cor. for 12 & 13, T29-2