

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6212)

Set a basalt stone 15x10x8 ins., 10" in the ground for cor. of secs. 6 and 7, T29S R1W only, marked with 1 notch on N. and 5 notches on S. edge; from which

- A Pine 18" dia., bears N.36°30'E., 73 lks. dist., mkd. T29S R1W S6 BT.
- A Fir 10" dia., bears S.45°30'E., 24 lks. dist. mkd. T29S R1W S7 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - April 27, 1978 - C.S. File 59/46-56

Found - Orig. corner stone set solidly in place and marked with one groove on the North face and five grooves on the South face. Stone measures 15" x 10" x 8".

14" Fir stump bears S.45°30'E., 15.6 ft. (Rec. 15.84') Open and find scribing and reverse "T29S"

Pine BT to the NE. is gone. Falls in landing.

The corner for secs. 1 and 12, T29-2 is a brass cap set by GLO, bears S.1°15'W., 8.1 ft. (Rec. South 7.92')

Moving the orig. corner stone aside, I SET in its place a 2½" brass cap on a 1" I.P. stamped: County Surveyors Office 1978

T 29 S
|
S 6
|
S 7

I bury the corner stone along side the iron pipe.

New Accessories:

- A 5/8" Iron rod with a 1½" alum. cap bears N.48°E., 12.4 ft. stamped "R.M. S 48 W 12.4" with an arrow pointing to the corner.
- A 5/8" Iron rod with a 1½" alum. cap bears S.21°30'E., 28.5 ft. stamped: "R.M. N 21½ W 28.5" with arrow pointing to the corner.

No trees available for BTs.

Corner is located 40 ft. N. of F.S. Road. #2846 & in a clearcut.