

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & S. 6, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6059)

-----  
Set ¼ sec. post, from which  
A Fir 10" dia., bears S.88°W., 48 lks. dist.  
A Fir 24" dia., bears N.70°W., 33 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Aug. 1, 1960 - C.S. File 51/121-1

-----  
Determined by old BTs:  
30" Fir stump, logged, bears N.70°W., 21.8 ft.  
30" Fir stump, logged, bears S.88°E., 31.8 ft.  
At corner point, SET 1" x 30" Iron rod, from which  
15" Sugar Pine S.15°W., 9.0 ft. mkd. ¼ S6 BT.  
12" Fir bears N.75°W., 19.0 ft. mkd. ¼ S31 BT.  
8" Fir bears N.4°E., 17.4 ft. mkd. ¼ S31 BT.  
14" Alder bears S.67°E., 7.5 ft. mkd. ¼ S6 BT.

Survey by J.A. Hoffbuhr - For: Umpqua National Forest - July 2, 1970 - C.S. File 55/158 and M 40-4

-----  
Found - 1" dia. Iron rod.  
Replaced rod with a 2" dia. Pipe with 2½" brass disk, stamped:  
T 29 S R 1 W  
¼ S 31  
S 6  
T 30 S R 1 W  
R.L.S. 222  
1970

from which bears  
12" Fir N.4°E., 17.4 ft. shows good scar.  
Orig. BT found, 30" stump, S.88°E., 31.8 ft.  
14" Alder S.66°E., 7.2 ft. scribes visible.  
21" Sugar Pine S.15°W., 8.7 ft.  
14" Fir N.75°W., 18.6 ft.  
Orig. BT found, 30" Fir stump, N.70°W., 21.8 ft.

BLM Resurvey by Donovan C. Harris, Cadastral Surveyor, under Group #748, Surveyed Aug. 1971 - (DCSO records Vol. 35 Page(s) 14583-84)

-----  
The ¼ sec. cor. of secs. 6 and 31, perpetuated and recorded by Markham in 1960, subsequently remonumented by Hoffbuhr in 1970, with an iron post 2½" dia., firmly set, extending 12" above ground with cap as marked in 1970, from which the remaining original bearing tree  
(Cont. Next Page)

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & S. 6, T30-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir stump 30" dia., bears N.70°W., 33 lks. dist. mkd. with rotted face.

and bearing trees mkd. by Markham

A Fir 10" dia., bears N.2°E., 26 lks. dist. mkd. with healed blaze.

An Alder 14" dia., bears S.65°E., 11 lks. dist. with scribe marks  $\frac{1}{4}$  S6 visible on partly healed blaze.

A Pine 22" dia., bears S.15½°W., 14 lks. dist. mkd. with healed blaze.

A Fir 16" dia., bears N.76°W., 29 lks. dist. mkd. with healed blaze.

A careful search was made for the  $\frac{1}{4}$  sec. cor. established by F. Mensch. No evidence was found.

Cor. falls in a dense stand of timber and scattering undergrowth.

(Note: With material furnished me, I found no Mensch corner information for this  $\frac{1}{4}$  corner.) V.Laugen, Aug. 1997

Fd. OK, Sept. 1993 by H. Pieske - M 117-62

David Edwards - For: Roseburg Resources Co - 12/2017 - M174-2

Found - Brass cap per M40-4  
20" dia., Fir stump bears N.2°E., 17.2'  
30" dia., Pine snag bears S.15½°W., 9.2'  
29" dia., Fir bears N.76°W., 19.1'  
All with healed blaze.

New - A six ft steel post is set 2 ft East.