

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6092)

-----  
Set a basalt stone 18x10x10", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A R.Fir, 30" dia., bears N.60°E., 77 lks., mkd: ¼ S30 BT.

A R.Fir, 30" dia., bears S.3°E., 99 lks., mkd: ¼ S31 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-25

-----  
Found - 18x10x10 stone "¼" on north side.  
30" now 39" D.Fir N.60°E., 50.8 ft. shows good scar.  
30" now 40" D.Fir S.3°E., 65.3 ft. opened for scribe  
"BT"

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE ¼ S 30  
1969 S 31

New BTs- 7" D.Fir N.67°E., 13.5 ft. mkd: "¼ S30 CS BT"  
12" D.Fir S.35 7/8°E., 15.1 ft. mkd: "¼ S31 CS BT"