

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6095)

Set a basalt stone 15x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which

A W.Fir, 10" dia., bears N.27°E., 45 lks., mkd: 1/4 S19 BT.

A W.Fir, 30" dia., bears S.7°W., 32 lks., mkd: 1/4 S30 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-23

Found - No trace of corner stone nor NE BT
30" W.Fir, now stump, S.7°W., 21.1 ft., opened for scribe "1/4 S B"

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1/4 S 19
1969 S 30

New BTs- 14" Cedar N.18°W., 80.4 ft. mkd: 1/4 S19 CS BT

10" Cedar N.52°W., 85.9 ft. mkd: 1/4 S19 CS BT

This corner lies in large cut unit. No other trees available.