

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6101)

Set a porphyry stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A R.Fir, 30" dia., bears N.60°E., 26 lks., mkd: ¼ S7 BT.

A R.Fir, 20" dia., bears S.69°E., 34 lks., mkd: ¼ S18 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6159)

Intersect the old ¼ sec. cor. which is a porphyry stone, 12x8x6", firmly set, marked & witnessed as described by the surveyor general. I change this cor. to refer to sec. 18 only, obliterate marks on the NE BT, & reset the stone 8" in the ground, marked ¼ S18 n S face, from which

A R.Fir, 20" dia., bears S.69°E., 34 lks., mkd: ¼ S18 BT.
(Old BT)

A chinquapin, 6" dia., bears S.9°W., 43 lks., mkd: ¼ S18 BT. (New BT)

S¼ cor. Sec. 7 only bears S.89°45'W., 0.72 chains.