

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6089)

Set a basalt stone 18x12x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A laurel, 12" dia., bears S.78°E., 17 lks., mkd: ¼ S32 BT.
A R.Fir, 24" dia., bears N.60°W., 54 lks., mkd: ¼ S31 BT.

J.A. Hoffbuhr - For: Umpqua National Forest - July 2, 1970 - C.S. File 55/158 - M40-4

Found - 18x12x8" basalt stone in place with ¼ scribed on west face.
Orig. BT A 14" madrona down on face & rotten S.78°E., 11.2'.
New - Replaced stone with a 2" dia., pipe with a 2½" dia. brass disk stamped
T29S R1W
¼ S 31|S 32
RLS 222
1970

from which bears scribed new BTs:
9" Fir scribed (¼ S32 BT) N.83½°E., 50.5 ft.
8½" Madrona scribed (¼ S31 BT) N.87°W., 40.2 ft.
Buried orig. stone monument alongside pipe.

Leonard Herzstein, USFS & Deputy Co. Surveyor - J. Landrum - T. Wolford - April 28, 1981 - C.S. File 61/19-51

Found - 2" IP with brass cap properly marked, firmly set, projecting 6" above ground, with orig. basalt stone alongside.
Orig. BT, a roothole, S.78°E., 11.2 ft. with a rotten madrone of indeterminate size alongside with no marks visible.
13" D.Fir N.83½°E., 50.5 ft. with healed double blaze.
9" madrone snag, N.87°W., 40.0 ft. with S.M. "¼ S31 BT" visible on partly healed double blaze. (Rec. 40.2 ft.)
New BTs- 6" D.Fir S.16°W., 39.9 ft. mkd: "¼ S31 CS BT" on double blaze.