

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6090)

Set a basalt stone 15x10x4", 10" in the ground for cor. of secs. 29, 30, 31, & 32 mkd with 1 notch on S & 5 notches on E edge, from which

- A laurel, 6" dia., bears N.8°E., 37 lks., mkd: T29S R1W S29 BT.
- A laurel, 6" dia., bears S.81°E., 28 lks., mkd: T29S R1W S32 BT.
- A laurel, 6" dia., bears S.52°W., 30 lks., mkd: T29S R1W S31 BT.
- A R.Fir, 6" dia., bears N.20°W., 26 lks., mkd: T29S R1W S30 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-12

Found - 6" now 17" D.Fir, N.20°W., 17.2 ft. shows good scar.
6" now 12" laurel, S.52°W., 19.8 ft. scribe visible, "29".

6" now 9" Laurel, S.81°E. 18.5 ft., scribe visible.
6" Laurel, now down, N.8°E. 24.4 ft., down on face.

Set - Brass Cap at Cor. Mkd: County Surveyors T29S R1W
Office S 30 | S 29
1969 S 31 | S 32

Reblazed & Rescribed:
12" Laurel S.52°W. 19.8 ft. mkd: T29S R1W S31 CS BT.
New BTs- 9" D.Fir S.65°E. 9.6 ft. mkd: T29S R1W S32 CS BT.
17" Cedar N.44°E. 46.4 ft. mkd: T29S R1W S29 CS BT.

Fd. Ok by L. Herzstein, 5/18/1981 - C.S. 61/24-12