

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6092-3)

-----  
Set a porphyry stone 15x8x5", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which  
A R.Fir, 40" dia., bears N.43°E., 50 lks., mkd: 1/4 S29 BT.  
A cedar, 18" dia., bears N.45°W., 13 lks., mkd: 1/4 S30 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 4, 1969 - C.S. File 54/82-81

-----  
Found - 40" D.Fir, now stob, N.43°E., 33.0. Scribe visible 1/4 S 29 BT.  
18" Cedar, now down, N.45°W., 8.6. Tree lying on face & rotting.  
15x8x5 stone firmly set at 1/4 cor. mkd. 1/4 on W face.  
Set brass cap at 1/4 cor. mkd: COUNTY SURVEYORS OFFICE 1969  
T29S R1W  
S 30 | S 29  
New BTs- 12" R.Fir N.33°E., 34.6 ft. scribed 1/4 S29 CS BT.  
10" Cedar S.73°W., 16.7 ft. scribed 1/4 S30 CS BT.

Fd. Ok L. Herzstein 5/18/1981 - C.S. File 61/24-22

David Edwards - April 2010 - C.S. File 65/69-15

-----  
Found - 1969 County Surveyor brass cap. Good.  
11" dia. dead W.Fir bears N.33°E., 34.5' with healed blaze.  
14" dia. Cedar bears S.74°W., 16.7' with healed blaze.  
New BTs- A 6" dia. Cedar scribed 1/4 S29 BT bears N.88°E., 20.2 ft.  
A 6 foot steel post is set 2 feet North  
BT measured to side-center.  
Comp. decl. 18°