

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6093)

Set a porphyry stone 15x10x8", 10" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edge, from which

- A sugar pine, 18" dia., bears N.44°E., 232 lks., mkd: T29S R1W S20 BT.
- A laurel, 8" dia., bears S.88°E., 196 lks., mkd: T29S R1W S29 BT.
- A R.Fir, 6" dia., bears S.51°W., 284 lks., mkd: T29S R1W S30 BT.
- A laurel, 18" dia., bears N.25°W., 244 lks., mkd: T29S R1W S19 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 4, 1969 - C.S. File 54/82-80

Found - 18" Pine, now 41" N.44°E., 153.1. Shows scar.
8" Laurel, now 14" S.88°E., 129.0. Shows old axe work rotten face.
6" D.Fir, now 15, S.51°W., 186.6. Shows scar.
18" Laurel, now stump hole, N.25°W., 160.4.
15x10x8 stone firmly set at sec. cor. mkd. 5 notches on the East 2 South.

Set brass cap at sec. cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 19|S 20
S 30|S 29

New BTs- 19" D.Fir S.59°W., 15.8 scribed T29S R1W S30 CS BT.
19" D.Fir N.48°W., 8.7 scribed T29S R1W S19 CS BT.
12" D.Fir S.68°E., 5.2 scribed T29S R1W S29 CS BT.
12" Cedar N.58°E., 20.1 scribed T29S R1W S20 CS BT.

Fd. OK L. Herzstein, 5/18/1981 - C.S. File 61/24-21