

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6096)

Set a porphyry stone 18x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A R.Fir, 12" dia., bears S.56°E., 113 lks., mkd: ¼ S20 BT.

A laurel, 8" dia., bears N.72°W., 82 lks., mkd: ¼ S19 BT.

J.A. Hoffbuhr - For: Umpqua National Forest - Sept. 1970 - C.S. File 55/168 - M42-7

Found - 6x8" stone 10" above ground & firmly in place with "¼" scribed on West face.

Set - 2" dia., iron pipe with 2½" dia., brass disk stamped:

T29S R1W

¼ S 19|S 20

RLS 222

1970

from which bears

6" D.Fir scribed "¼ S19 BT" bears N.20°W., 21.5'

7' D.Fir scribed "¼ S20 BT" bears S.52°E., 9.7'