

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6096)

-----  
Set a basalt stone 16x10x5", 11" in the ground for cor. of secs. 17, 18, 19, & 20 mkd with 3 notches on S & 5 notches on E edge, from which

- A R.Fir, 36" dia., bears N.46°E., 90 lks., mkd: T29S R1W S17 BT.
- A R.Fir, 40" dia., bears S.12°E., 37 lks., mkd: T29S R1W S20 BT.
- A R.Fir, 36" dia., bears S.50°W., 82 lks., mkd: T29S R1W S19 BT.
- A R.Fir, 36" dia., bears N.43°W., 26 lks., mkd: T29S R1W S18 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-16

-----  
Found - 16x10x5 stone at corner, notches visible, 5 on E & 3 on S.

- 36" D.Fir now snag, N.46°E., 59.4 ft shows good scar
- 40" now 55" D.Fir, S.12°E., 24.4 ft. shows good scar
- 36" D.Fir now stob, S.50°W., 54.1 ft shows good scar
- 36" now 44" D.Fir, N.43°W., 17.2 ft. pitched over, scribing visible.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE S 18 | S 17  
1969 S 19 | S 20

New BTs- 6" D.Fir S.83°W., 7.0 ft. mkd: T29S R1W S19 CS BT  
12" D.Fir N.60°E., 33.1 ft. mkd: T29S R1W S17 CS BT