

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6099)

Set R.Fir, 30 dia., for ¼ sec. cor. I mark ¼ S 18 on W & 17 on E side, from which

A R.Fir, 20" dia., bears N.22°E., 32 lks., mkd: ¼ S17 BT.

A Hemlock, 8" dia., bears S.8°W., 26 lks., mkd: ¼ S18 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-46

Found - 30" D.Fir corner tree, now shows good scars on E & W sides.

20" now 29" D.Fir N.22°E., 21.1 ft. shows good scar.

8" Hemlock, now down, S.8°W. 17.2 ft scribe visible.

Set brass cap on S side of cor. tree mkd:

COUNTY SURVEYOR T29S R1W

OFFICE 1969 ¼ S 18 | S 17

New BT - 14" Hemlock S.55°E., 56.4 ft. mkd: ¼ S17 CS BT.

No trees available in west quadrant, S18.