

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T28-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5366)

- 
- Set a basalt stone 20x14x6 ins., 15" in ground for cor. of secs. 5, 6, 31 and 32, marked with 5 notches on E. and 1 notch on W. edges; from which
- A Fir 12" dia., bears N.75°E., 15 lks. dist. mkd. T28S R1W S32 BT.
  - A Fir 14" dia., bears S.52°E., 41 lks. dist. mkd. T29S R1W S5 BT.
  - A Fir 14" dia., bears S.2°W., 25 lks. dist. mkd. T29S R1W S6 BT.
  - A Fir 10" dia., bears N.80°W., 24 lks. dist. mkd. T28S R1W S31 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6146-47)

- 
- Intersect the old cor. of secs. 5, 6, 31 and 32, which is a basalt stone 5x14x6 ins. above ground, firmly set, marked with 5 notches on E. and 1 notch on W. edge, and witnessed as described by the surveyor general. I change this cor. to refer to secs. 31 and 32 only, and obliterate the marks on the old SE. and SW. bearing trees. The cor. is now witnessed as follows:
- A Fir 16" dia., bears N.75°E., 15 lks. dist. mkd. T28S R1W S32 BT. (old BT)
  - A Fir 14" dia., bears N.30°W., 24 lks. dist. mkd. T28S R1W S31 BT. (Old BT) The bearing of this tree was erroneously reported N.80°W.