

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6091)

N.89°53'E., on a random line bet. secs. 29 & 32
39.62 chs.
The cor. which I established in my orig. survey under contract No. 757 as the ¼ sec. cor. bet. secs. 29 & 32 bears N. 15 lks. I destroy the cor. & marks on BTs
39.98 chs.
Set an ironstone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A madrone, 9" dia., bears N.9°E., 57 lks., mkd: ¼ S29 BT.
 A madrone, 6" dia., bears S.83°E., 10 lks., mkd: ¼ S32 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-13

Reported as not found.
Found - Old orig. fir destroyed in 1905. New cor. set 26 lks., west. Two Laurel BTs probably fell in old rd.
No trace of cor. stone or any other evidence.

J.A. Hoffbuhr - For: Umpqua National Forest - July 2, 1970 - C.S. File 55/158 - M40-4

Set - 2" dia., pipe with 2½" brass disk stamped:
 T29S R1W
 ¼ S 29
 S 32
 RLS 222
 1970 from which bears scribed New BT
 A 6" dia., madrona scribed (¼ S29 BT) N.13½°E., 37.1'
 A 13" dia., madrona scribed (¼ S29 BT) S.7¼°E., 43.6'

Leonard Herzstein, USFS & Deputy Co. Surveyor - Witnesses: J. Landrum & T. Wolford - April 29, 1981 - C.S. File 61/19-57

Found - 2" IP with properly marked brass cap, firmly set, projecting 6" above ground. 1970
 6" madrone snag, N.13°E., 37.1 ft with SM "¼ S29 BT" visible on partly healed double blaze. 1970
 14" madrone snag, S.7½°E., 43.6 ft with SM "¼ S32 BT" visible on partly healed double snag.
New BTs- 9" W.Fir N.67°E., 23.4 ft. mkd: "¼ S29 CS BT" on double blaze.
 6" D.Fir S.21°E., 68.3 ft. mkd: "¼ S32 CS BT" on double blaze.

CONT.

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Leonard Herzstein, USFS - Feb. 22, 2011 - C.S. File 65/72-6

Found - BC & 3 BTs.

Note - No new measurements were taken for this corner renewal. This report is only to document the 1970 BT (10" dia. madrone, N.13°E., 37.1 ft. with healed double blaze. Tree sprouted a new top and is alive.) is healthy.

Russell Badgley - 7/2021 - C.S. File 65/109-26

Found - A 2" iron post, firmly set per M40-4, projecting 6" above the ground with a 2½" dia. brass cap (properly) marked

BTs by Hoflbuhr in 1970 -

An 11" dia. madrone bears N.12°15'E., 37.1 ft. (Rec. N.13½°E., 37.1 ft.)

BTs by Hertzstein in 1981 -

A 12" dia. D.Fir w/healed double blaze bears S.22°00'E., 68.4 ft. (Rec. S.21°E., 68.3 ft.)

A 14" dia. W.Fir w/healed double blaze bears N.66°00'E., 23.5 ft. (Rec. N.67°E., 23.4 ft.)

New - A 13" dia. D.Fir bears S.81°00'W., 34.9 ft scribed "N ¼ S32" & "BT" on a double blaze, with a 1" brass washer stamped "BADGLEY PLS70716" nailed into the lower blaze.

Note - Compass declination: 14°30'E.