

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6094)

Set a porphyry stone 16x8x8", 11" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
A R.Fir, 10" dia., bears N.43°W., 7 lks., mkd: 1/4 S20 BT.
A R.Fir, 6" dia., bears S.55°W., 31 lks., mkd: 1/4 S29 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-13

Reported as not found.
Found - Forest location poster near 1/4 cor. Old rail fence line running North-South & West. No evidence.

J.A. Hoffbuhr - For: Umpqua National Forest - Sept. 1970 - C.S. File 55/168 - M42-7

Corner set by proportionate measurement.
Set - 2" dia., iron pipe with 2 1/2" dia., brass disk stamped:
T29S R1W
1/4 S 20
S 29
RLS 222
1970 from which bears
10" W.Fir scribed 1/4 S20 BT, bears N.4°E., 13.7'
6" Ash scribed 1/4 S29 BT, bears S.26°W., 14.5'

Leonard Herzstein, USFS & Deputy Co. Surveyor - Witnesses: Jim Landrum & Tom Wolford - May 1981 - C.S. File 61/24-8

Found - 2" dia., IP, firmly set, projecting 4" above ground, set by J.A. Hoffbuhr, RLS 222, in 1970, with BC properly marked. BTs mkd by Hoffbuhr in 1970:
14" D.Fir N.4°E., 13.7 ft. (Rec. W.Fir) with healed double blaze.
10" Ash stump, S.26°W., 14.5 ft. with scribe marks "1/4 S29 BT" visible on partly healed double blaze.
New BT - 13" D.Fir S.40°E., 26.4 ft., scribed "1/4 S29 CS BT" on double blaze.
Note - Corner is about 40 ft. north of private road.

David Edwards - April 2010 - C.S. File 65/69-14

Found - 2" dia., iron pipe with brass cap. Good.
15" dia., D.Fir with healed blaze bears N.4°E., 13.7 ft.
continued next page

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - A broken off 14" dia., D.Fir with healed blaze bears
S.40°E., 26.4 ft.
6" dia., D.Fir scribed ¼ S20 BT bears N.77°W., 15.7
ft.
6 ft. steel post is set 2 ft. South.
Compass decl. 18°