

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6097)

Set a basalt stone 15x12x10", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A R.Fir, 36" dia., bears N.35°E., 8 lks., mkd: ¼ S17 BT.

A Cedar, 18" dia., bears S.43°W., 46 lks., mkd: ¼ S20 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-47

Found - 36" D.Fir, now 41", shows good scar.

18" Cedar, now 34", shows good scar & part of rotten face.

15x12x10 stone mkd: ¼ on W face.

Set brass cap at ¼ cor. mkd: COUNTY SURVEYOR T29S R1W
OFFICE 1969 ¼ S 17|S 20

Reblazed & rescribed -

34" Cedar S.43°W., 30.4 ft. mkd: "¼ S20 CS BT"