

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 17 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6100)

Set a basalt stone 18x10x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A W.Fir, 24" dia., bears N.9°W., 40 lks., mkd: ¼ S8 BT.
 A W.Fir, 18" dia., bears S.57°W., 20 lks., mkd: ¼ S17 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6160-1)

Intersect the old ¼ sec. cor., which is a basalt stone, 18x10x8" firmly set, marked & witnessed as described by the surveyor general. I obliterate the marks on the NW BT & change this cor. to refer to sec. 17 only. Reset the stone, 12" in the ground, marked ¼ S17 on S face, from which
 A fir, 6" dia., bears S.43°E., 21 lks., mkd: ¼ S17 BT.
 (New BT)
 A W.Fir, 20" dia., bears S.57°W., 20 lks., mkd: ¼ S17 BT.
 (Old BT)
S¼ sec. 8, only, bears N.88°55'W., 1.34 chains