

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 271700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T28-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5366)

Set a basalt stone 20x12x10 ins., 15" in ground for ¼ sec. cor. mkd. ¼ sec. cor. on N. face; from which

A Pine 16" dia., bears N.56°E., 50 lks. dist., mkd. ¼ S5 BT.

A Fir 14" dia., bears S.10°W., 34 lks. dist., mkd. ¼ S5 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6147-48)

Intersect the old ¼ sec. cor., which is a basalt stone, 5x12x10 ins. above ground, firmly set, marked ¼ on N. face, and witnessed as described by the surveyor general. I change this cor. to refer to sec. 32 only, obliterated the marks on the old SW. bearing tree and mark a new tree as follows:

A Pine 16" dia., bears N.56°E., 50 lks. dist. mkd. ¼ S32 BT. (Old BT)

A Pine 10" dia., bears N.44°W., 13 lks. dist. mkd. ¼ S32 BT. (New BT)