

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 278500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8 & 9 (South) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6161)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8 & 9, with brass cap mkd

T29S R1W
S 8|S 9

17
1922

from which

A yew, 7" dia., bears N.13°E., 28 lks. mkd: T29S R1W S9 BT

A cedar, 18" dia., bears N.47°W., 28 lks., mkd: T29S R1W S8 BT.

(North Cor. Secs. 16 & 17, only, bears S.88°55'E., 1.58 chs.)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-20

Found - Orig. 8" now 10" yew, N.13°E., 18.5 ft. scribed visible.

Orig. cedar, now down, on face.

GLO 1922 Brass cap, properly marked.

New BT - 26" Maple N.36°W., 52.4 ft. mkd. T29S R1W S8 CS BT.

Note - This corner lies 103 ft. west of corner to secs. 17 & 16 only.