TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6068) and Pg. 6070)

(Page 6070) (80.00 chs.)
Set a basalt stone 20x12x10 ins., 15" in the ground for cor. of secs. 4, 5, 32 and 33, marked with 4 notches on E. and 2 notches on W. edges, from which

A W.Oak 8" dia., bears N.38°E., 72 lks. dist. mkd. T29S R1W S33 BT.
A Fir 20" dia., bears S.55°E., 8 lks. dist. mkd. T30S R1W S4 BT.
A Fir 12" dia., bears S.28°W., 27 lks. dist. mkd. T20S R1W S5 BT.
A Fir 10" dia., bears N.81°W., 53 lks. dist. mkd. T29S R1W S32 BT.

(Page 6068-69) (0.58 chs.)
The cor. which I established under contract No. 757 as the cor. of secs. 4, 5, 32 and 33, bears N. 34 lks. dist., I destroy the cor. and marks on bearing trees.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 27, 1967 - C.S. File 54/59-13

Found - 20x12x10 stone mkd. 4 notches on W. side & 2 notches on East.
Orig. 8" now 9" W.Oak N.38°E., 47.5 ft., opened for scribe.
Orig. 12" now down D.Fir, S.28°W., 17.8 ft., opened for scribe.
Orig. 20" now 24" D.Fir S.55°E., 5.3 ft., shows good scar.
Orig. 10" now 15" D.Fir N.81°W., 35.0 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 1 W

S 32	S 33
S 5	S 4

1967

New BTs- 16" D.Fir S.62°W., 41.4 ft. mkd. T30S R1W S5 CS BT.
8" S.Fir N.16°E., 29.6 ft. mkd. T29S R1W S33 CS BT.