

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6081)

Set a basalt stone 15x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A W.Fir, 18" dia., bears N.48°E., 31 lks., mkd: 1/4 S33 BT.

A W.Fir, 18" dia., bears S.58°W., 59 lks., mkd: 1/4 S32 BT. N.0°3'W. 0.25 chs.

The corner established by me in my orig. survey under contract No. 757 as the 1/4 sec. cor. bet. secs. 32 & 33, bears E 50 lks. I destroy the cor. and marks on BTs. (There is a record of Mensch's orig. survey on the internet)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-35

Found - 15x8x6 stone mkd: "1/4" on W face, firmly in place. 18" W.Fir now down, N.48°E., 20.5 ft. opened for scribe 1/4 S.

18" W.Fir now down, S.58°W., 38.9 ft.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W OFFICE 1969

1/4 S 32 | S 33

New BTs- 13" W.Fir S.50°W., 12.8 ft. mkd: "1/4 S32 CS BT"

10" D.Fir N.23°E., 4.5 ft. mkd: "1/4 S33 CS BT"

Charles H. Hurst - For: US Forest Service - Oct. 20, 1975 - M58-38

Found - 1969 County Surveyor BC 1" IP mon., stone alongside mkd. "1/4"

10" D.Fir N.23°E., 4.5 ft.

11" W.Fir dead, S.46°W., 12.8 ft.

New BT - 17.3" W.Fir, S.60°W., 19.8 ft. "1/4 32 BT"