TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6081)

Set an ironstone 16x10x8", 11" in the ground for cor. of secs. 28, 29, 32, & 33 mkd with 4 notches on E & 1 notch on S edge, from which

A W.Fir, 40" dia., bears N.31°E., 11 lks., mkd: T29S R1W S28 BT.
A W.Fir, 12" dia., bears S.66°E., 42 lks., mkd: T29S R1W S33 BT.
A W.Fir, 8" dia., bears S.63°W., 40 lks., mkd: T29S R1W S32 BT.
A R.Fir, 36" dia., bears N.32°W., 70 lks., mkd: T29S R1W S29 BT.

N.89°53'E. 0.14 chs. on a random line bet. secs. 28 & 33 Intersect N & S line, 26 lks. S. of the cor. of secs. 27, 28, 33, & 34, established by me in my orig. survey under contract No. 757. (There is a record of Mensch's orig. survey on the internet)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-36

Found - 16x10x8 stone, firmly set with 4 notched on E & 1 on south.
36" now 48" D.Fir N.32°W., 46.2 ft. opened for scribe.
12" now 16" W.Fir S.66°E., 27.7 ft. shows good scar.
No trace of NE or SW BTs

Set brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1969

T29S R1W

S 29	S 28
S 32	S 33

New BTs- 16" Cedar S.29½°W., 31.7 ft mkd: T29S R1W S32 CS BT.
25" W.Fir N.27½°E., 42.8 ft mkd: T29S R1W S28 CS BT.