

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6083)

Set a basalt stone 18x12x10", 12" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on S & 4 notches on E edges, from which

- A R.Fir, 10" dia., bears N.50°E., 229 lks., mkd: T29S R1W S21 BT.
- A R.Fir, 24" dia., bears S.75°E., 170 lks., mkd: T29S R1W S28 BT.
- A Cedar, 8" dia., bears S.50°W., 72 lks., mkd: T29S R1W S29 BT.
- A R.Fir, 14" dia., bears N.81°W., 81 lks., mkd: T29S R1W S20 BT.

Douglas Co. Surveyors Office - Frank Jones & W. Penley - May 21, 1969 - C.S. File 54/82-63

Found - No trace of 18x12x10 corner stone, because the cor. falls in an old skid road. Found two good BTs.
8" cedar, now 22" S.50°W., 47.5 ft. shows good scribe of (T2,R,)
14" R.Fir, now 32" N.81°W. 53.5 ft. Show, good face.
10" R.Fir, now 28" stump, N.50°E., 151.4 ft. Cut too low to show face or scribing.
24" R.Fir now 42" stump S.75°E., 112.2 ft. shows scribe of a (W)

Set brass cap at sec. cor. from bearing & dist from BTs (mkd)

COUNTY SURVEYORS	T29S	R1W
OFFICE 1969	<u>S 20</u>	<u>S 21</u>
	S 29	S 28

New BTs- 6" D.Fir N.52½°E. 23.2 ft scribed: T29S R1W S21 CSBT
14" D.Fir S.55°E. 23.4 ft scribed: T29S R1W S28 CSBT

Note - This corner lies in a skid road on top a ridge with logged unit to the East.

Leonard Herzstein, USFS & Dep. Co. Surveyor - Jim Landrum - Tom Wolford - May 5, 1981 - C.S. File 61/24-3

Found - 1" IP firmly set, projecting 12" above a 3 ft. dia. mound of stone, with B.C. marked County Surveyors Office 1969 T29S R1W S20 S21 S29 S28.

OBTs - 28" D.Fir stump bears N.50°E., 151.4 ft., with no marks visible.
42" D.Fir stump bears S.75°E., 112.2 ft. with healed lower blaze.
27" I.Cedar bears S.50°W, 47.5 ft., with healed blaze. continued next page

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

32" D.Fir stump bears N.81°W., 53.5 ft., with healed blaze.

1969 BTs- 10" D.Fir bears N.52½°E., 23.7-ft. (Rec. 23.2 ft), with healed double blaze.

21" D.Fir bears S.55°E., 23.4 ft., with healed double blaze.

Set - Guard post 5 ft. North of BC with USFS signs #S4-2, and #S4-4 attached

New BT - 6" D.Fir bears N.59°W., 21.6 ft., scribed T29S R1W S 20 CS BT on double blaze.

2