

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6085)

Set a porphyry stone 18x15x6", 12" in the cruiser for ¼ sec. cor. mkd. ¼ on W face, from which

A W.Fir, 12" dia., bears S.26°E., 40 lks., mkd: ¼ S21 BT.

A Yew, 8" dia., bears S.10°W., 32 lks., mkd: ¼ S20 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-15

Not found

Found 2 cedars with cruisers marks. Cor. Apparently in old skidding area.

J.A. Hoffbuhr - For: Umpqua National Forest - Sept. 3, 1970 - C.S. File 55/168 - M42-7

Set by proportionate measurement

Set - 2" iron pipe with 2½ brass disk stamped:

T29S R1W

S 20|S 21

RLS 222

from which bears:

12" W.Fir scribed "¼ S21 BT" bears N.74°E., 22.2 ft.

10" W.Fir scribed "¼ S20 BT" bears N.63°W., 27.3 ft.

Leonard Herzstein, USFS & Deputy Co. Surveyor - Witnesses: Jim Landrum & Tom Wolford - May 1981 - C.S. 61/24-14

Found - 2" I.P. firmly set, projecting 4" above ground, set by J.A. Hoffbuhr, OLS# 222, in 1970, with BC properly marked.

BTs marked by Hoffbuhr in 1970

An 18" D.Fir (Rec. W.Fir), N.74°E., 22.2 ft., with healed double blaze.

A 10" W.Fir snag, N.63°W., 27.3 ft., with scribe marks "¼ S20 BT" visible on partly healed double blaze.

New - I mark new BT:

A 5" W.Fir, S.70°W., 43.2 ft., scribed "¼ S20 CS BT" on double blaze.