

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6085)

-----  
Set a porphyry stone 15x12x8", 10" in the ground for cor. of secs. 16, 17, 20, & 21 mkd with 3 notches on S & 4 notches on E edge, from which

- A R.Fir, 36" dia., bears N.44°E., 75 lks., mkd: T29S R1W S16 BT.
- A R.Fir, 30" dia., bears S.32°E., 67 lks., mkd: T29S R1W S21 BT.
- A W.Fir, 18" dia., bears S.42°W., 48 lks., mkd: T29S R1W S20 BT.
- A R.Fir, 10" dia., bears N.29°W., 49 lks., mkd: T29S R1W S17 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-14

-----  
Found - No trace of stone at corner.  
36", now 50" D.Fir N.44°E., 49.5 ft shows good scar.  
10", now 16" D.Fir N.29°W., 32.3 ft shows good scar.  
30" D.Fir, now stump, S.32°E., 44.2 ft. opened for scribe "S21".  
18" W.Fir, now burnt stump, S.42°W., 31.7 ft.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE S 17 | S 16  
1969 S 20 | S 21

New BTs- 6" R.Fir S.31°E., 33.8 ft. mkd: T29S R1W S21 CS BT.  
13" Y.Pine S12°W., 44.3 ft. mkd: T29S R1W S20 CS BT.

-----  
Leonard Herzstein, USFS & Deputy Co. Surveyor - Witnesses:  
Jim Landrum & Tom Wolford - May 1981 - C.S. 61/24-18

-----  
Found - 2" IP set by Douglas County Surveyors Office in 1969, firmly set, projecting 4" above ground, with BC properly marked.

Orig BTs- A 50" D.Fir snag, N.44°E., 49.5 ft., with healed double blaze.  
A 30" D.Fir stump, S.32°E., 44.2 ft., with scribe mark "S21" visible on previously opened blaze.  
A 16" D.Fir snag, N.29°W., 32.3 ft., with healed double blaze.

BTs marked by Doug. Co. Surveyors Office in 1969:  
An 8" W.Fir (Rec. R.Fir), S.31°E., 33.8 ft. with healed double blaze.  
A 14" Sugar Pine snag (Rec. Y.Pine), S.12°W., 44.3 ft., with scribe mark "T29S R1W S20 CS BT" visible on partly healed blaze. cont.

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- A 14" W.Fir, N.45°E., 29.7 ft., scribed "T29S R1W S16 CS BT" on double blaze.  
An 8" D.Fir, S.5°W., 40.1 ft., scribed "T29S R1W S20 CS BT" on double blaze.  
An 11" I.Cedar, N.50°W., 48.9 ft., scribed "T29S R1W S17 CS BT on double blaze.