

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6087)

-----  
Set a porphyry stone 18x15x4", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A R.Fir, 40" dia., bears S.88°E., 30 lks., mkd: ¼ S16 BT.  
A W.Fir, 14" dia., bears N.39°W., 36 lks., mkd: ¼ S17 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-18

-----  
Found - No trace of corner stone.  
14" now 30" W.Fir N.39°W., 23.8 ft. shows good scar.  
40" D.Fir, now snag, S.88°E., 19.8 ft. scribing visible.  
Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE 1969 ¼ S 17|S 16  
New BTs- 28" D.Fir S.31°E., 48.3 ft. mkd: "¼ S16 CS BT"