

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6173-4)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T29S R1W  
S 5 | S 4  
S 8 | S 9  
1922

from which

- A pine, 9" dia. bears N.79°E., 17 lks. mkd: T29S R1W S4 BT
- A fir, 12" dia., bears S.29°E., 8 lks. mkd: T29S R1W S9 BT
- A fir, 10" dia. bears S.22°W., 14 lks. mkd: T29S R1W S8 BT
- A fir, 7" dia., bears N.41°W., 29 lks. mkd: T29S R1W S5 BT