

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6082)

S.89°42'W., on a true line bet. secs. 28 & 33
39.85 chs.

The cor. which I established in my orig. survey under contract No. 757 as the ¼ sec. cor. bet. secs. 28 & 33, bears N.15 lks. I destroy the cor. & marks on BTs. (There is a record of Mensch's orig. survey on the internet)
40.00 chs.

Set a basalt stone 12x12x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 14" dia., bears N.36°W., 18 lks., mkd: ¼ S28 BT.

A fir, 14" dia., bears S.18°E., 22 lks., mkd: ¼ S33 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-34

Found - 14" D.Fir now stob, N.36°W., 11.9 ft scribe visible.
14" now 16" D.Fir, S.18°E., 14.5 ft shows good scar.
12x12x8" stone, no marks on stone.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE ¼ S 28
1969 S 33

New BT - 15" D.Fir N.76°E., 19.4 ft. mkd: "¼ S28 CS BT"