

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6084)

Set an ironstone 15x10x4", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A cedar, 36" dia., bears N.45°E., 41 lks., mkd: ¼ S21 BT.

A cedar, 24" dia., bears S.53°W., 20 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-1

Found - Orig. stone, set firmly at ¼ cor. mkd. "¼" on north face, stone 15x10x4

36" now 42" cedar N.45°E., 27.1 ft. shows good scar.

24" now 30" cedar S.53°W., 13.2 ft. shows good scar.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE ¼ S 21
1969 S 28

No new BTs marked, tagged trees.