

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6086)

-----  
Set a basalt stone 15x8x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A hemlock, 10" dia., bears N.80°W., 45 lks., mkd: ¼ S16 BT  
A W.Fir, 12" dia., bears S.75°W., 21 lks., mkd: ¼ S21 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-5

-----  
Not Found  
Cor. falls in heavily logged unit. 2 small trees (will look again)

-----  
J.A. Hoffbuhr - For: Umpqua National Forest - Sept. 3, 1970 - C.S. File 55/168 - M42-7

-----  
Set - 2" iron pipe with 2½ brass disk stamped:  
T29S R1W  
¼ S 16  
      S 21  
RLS 222  
1970 from which bears:  
12" W.Fir scribed "¼ S21 BT" bears S.40°W., 40.0 ft.  
6" W.Fir scribed "¼ S16 BT" bears N.5°E., 34.0 ft.