

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 16 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6088)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A R.Fir, 14" dia., bears N.69°E., 137 lks., mkd: ¼ S9 BT.

A dogwood, 7" dia., bears S.60°E., 57 lks., mkd: ¼ S16 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6162-3)

Intersect the old ¼ sec. cor., which is a basalt stone, 4x10x6" above ground, firmly set, marked and witnessed as described by the surveyor general, except the old bearing trees have been killed by fire. I change this cor. to refer to sec. 16 only; reset the stone, 8" in the ground, marked ¼ S 16 on S. face, from which

A sugar pine, 16" dia., bears S.12°E., 196 lks., marked ¼ S16 BT.

A fir, 18" dia., bears S.9°W., 178 lks., mkd: ¼ S16 BT.

I obliterate marks on the old NE BT.

(The S¼ cor. sec. 9 only bears N.89°41'W., 2.21 chs.)