

TOWNSHIP 29 RANGE 1 POINT IDENTIFIER # 378500

PRIMARY CORNER DESCRIPTION Sec. Cor. Secs. 9 & 10 (South) only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6163)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 9 & 10, with brass cap mkd
T29S R1W
S 9 | S 10
S 16
1922

From which
A fir, 12" dia. bears N.40°E., 27 lks mkd: T29S R1W S10 BT
A fir, 18" dia. bears N.38°W., 42 lks. mkd: T29S R1W S9 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-22

Found - 1922 USGLO brass cap, properly marked.
12" now 15" D.Fir N.40°E., 17.8 ft. shows good scar.
18" now 23" D.Fir N.38°W., 27.7 ft. shows good scar.
New BT - 7" D.Fir S.18½°W., 16.8 ft. mkd: T29S R1W S16 CS BT.
Note - This corner lies 128.7 ft. W of sec. cor. to secs. 15 & 16.