TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dept. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6076)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A R.Fir, 18" dia., bears N.38°E., 24 lks., mkd: ¼ S34 BT.
A Maple, 10" dia., bears N.86°W., 42 lks., mkd: ¼ S33 BT.

Fd. & used on GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6129)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 26, 1969 - C.S. File 54/82-71

Found - 18" D.Fir, now 25" N.38°E., 15.8' shows good scar.
10" Maple, now 14" N.86°W., 27.7' shows good scar.
12x10x6 stone at ¼ cor. mkd. ¼ on West face.
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 33|S 34
BTs Ok & tagged.
Note - Best way to reach this cor. by boat across South Umpqua River.