

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dept. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6077)

Set a diorite stone 20x12x10", 15" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A sugar pine, 50" dia., bears N.67°E., 20 lks., mkd: ¼ S27 BT.
A yellow pine, 36" dia., bears S.57°W., 125 lks., mkd: ¼ S28 BT.

FD. & used on GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6129)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1, 1969 - C.S. File 54/82-2

Found - 20x12x10" orig. stone, firmly set, mkd: "¼" on West face.
Orig. 50" S.Pine, now stump, N.67°E., 13.2 ft. scribed visible.
No trace of other orig. BT, location falls in road.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 28 | S 27
New BTs- 11" Sugar Pine, S.27°W., 18' scribed ¼ S28 CS BT.
9" D.Fir N.24°E., 11.4 scribed ¼ S27 CS BT
Note - Road 2827 bears West 50.0 ft.

Maurice E. Farr, LS 1181, USFS - Leonard Herzstein - Randy Lopez - Jan. 21, 1985 - C.S. File 62/26-1

Found - 1¼" outside dia. I.P., firmly set, projecting 15" above ground with County brass cap properly mkd. attached. 1969
Orig. stone 18x10x8" found lying along-side IP with marks "¼" visible.
50" S.Pine stump N.67°E., 12.9 ft. (rec. 13.2 ft.) with scribe marks "S 4 BT" visible on partially healed blaze. (orig.)
10" D.Fir, N.24°E., 11.4 ft. with healed double blaze. 1969
11" ponderosa pine snag (rec. Sugar pine) S.27°W., 18.0 ft. with scribe marks "CS" visible on partially healed double blaze. 1969
Add - 3 ft. dia. mound of stone. Iron pipe now projects 6" continued next page

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 16" D.Fir, N.27°W., 16.3 ft. scribed "¼ S28 BT" on a double blaze with a brass washer stamped "LS 1181" nailed flush to lower blaze.
Corner is 40 ft. east of USFS Rd. #2827. A steel fence post with USFS signs #54-2 and 1154-4 bears N.0¾°E., 4.0 ft.