

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6077-8)

-----

Set a porphyry stone 18x15x5", 12" in the ground for cor. of secs. 21, 22, 27, & 28 mkd with 2 notches on S & 3 notches on E edge, from which

- A R.Fir, 24" dia., bears N.31°E., 24 lks., mkd: T29S R1W S22 BT.
- A R.Fir, 12" dia., bears S.64°E., 26 lks., mkd: T29S R1W S27 BT.
- A R.Fir, 12" dia., bears S.75°W., 31 lks., mkd: T29S R1W S28 BT.
- A R.Fir, 10" dia., bears N.54°W., 29 lks., mkd: T29S R1W S21 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82

-----

- Found - Orig. 18x15x5 stone, firmly set mkd. with notches.  
Orig. 24" now 40" D.Fir N.31°E., 15.8 ft. shows good scar.  
Orig. 12" now 28" R.Fir S.64°E., 17.2 ft. shows good scar.  
Orig. 12" now 28" R.Fir S.25°W., 20.5 ft. scribe visible.  
Orig. 10" now 15" D.Fir N.54°W., 19.1 ft. scribe visible.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE S 21 | S 22  
1969 S 28 | S 27

New BT - 30" D.Fir S.15°W., 11.2 ft. mkd: T29S R1W S28 CS BT.  
All other BTs OK & tagged.