

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6078)

Set a porphyry stone 18x12x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A R.Fir, 20" dia., bears N.81°E., 91 lks., mkd: ¼ S22 BT.
A cedar, 24" dia., bears S.88°W., 44 lks., mkd: ¼ S21 BT.

FD. & used on GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6130)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 15, 1969 - C.S. File 54/82-10

Found - 18x12x8" Stone mkd: 4
24" now 30" Cedar, S.88°W., 29.0 ft, scribe visible,
"4 21 T"
20" now 36" D.Fir N.81°E., 60.1 ft. shows good scar.
Set Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 21|S 22
All BTs OK & tagged.