

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6078-9)

Set a basalt stone 15x12x5", 10" in the ground for cor. of secs. 15, 16, 21, & 22 mkd with 3 notches on S & E edges, from which

- A R.Fir, 40" dia., bears N.39°E., 100 lks., mkd: T29S R1W S15 BT.
- A sugar pine, 12" dia., bears S.64°E., 58 lks., mkd: T29S R1W S22 BT.
- A R.Fir, 30" dia., bears S.70°W., 48 lks., mkd: T29S R1W S21 BT.
- A R.Fir, 40" dia., bears N.45°W., 71 lks., mkd: T29S R1W S16 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-3

Found - Stone 15x12x5 set firmly at corner mkd with notches. 40" now 48" Fir, N.39°E., 66.0 ft. shows good scar. 12" now 42" S.Pine S.64°E., 38.3 ft shows faint scar 30" D.Fir, now stump S.70°E., 31.7 ft opened for scribe.

40" D.Fir now stump N.45°W., 46.9 ft.

Set Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 16 | S 15
S 21 | S 22

New BTs- 8" R.Fir N.83°W., 9.7 ft. mkd: T29S R1W S16 CS BT.
7" R.Fir N.21°E., 5.9 ft. mkd: T29S R1W S15 CS BT.
12" D.Fir S.68½°E., 38.0 ft mkd: T29S R1W S22 CS BT.