

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6079)

Set a basalt stone 12x10x5", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A R.Fir, 15" dia., bears N.12°E., 70 lks., mkd: 1/4 S15 BT.

A R.Fir, 36" dia., bears N.70°W., 23 lks., mkd: 1/4 S16 BT.

Fd. & used GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6131)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-4

Found - Orig. stone, firmly set (12x10x5) at corner mkd: "1/4" on west face.

Orig. 36" now 42" D.Fir N.70°W., 15.2 ft. shows good scar.

Orig. 15" now 21" D.Fir N.12°E., 46.2 ft. shows good scar.

All BTs OK & tagged.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 1/4
S 16|S 15