

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 15 & 16 (North) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 14 Page 6080)

Set a basalt stone 20x15x6", 15" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notched on E edge, from which

A R.Fir, 48" dia., bears N.13°E., 42 lks., mkd: T29S R1W S10 BT.

A R.Fir, 6" dia., bears S.10°E., 28 lks., mkd: T29S R1W S15 BT.

A maple, 6" dia., bears S.13°W., 94 lks., mkd: T29S R1W S16 BT.

A sugar pine, 15" dia., bears N.15°W., 27 lks., mkd: T29S R1W S9 BT.

Fd. & used on GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6127)

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6163)

Intersect the old cor. of secs. 9, 10, 15, & 16, which is a basalt stone 5x15x6" above ground, firmly set marked with 4 notches on S & 3 notches on E edges, witnessed as described by the surveyor general. I obliterate marks on the NE & NW BTs, change this cor. to refer to secs. 15 & 16 only, and mark 3 notches on W edge of stone, from which

A fir, 10" dia., bears S.10°E., 28 lks., mkd: ¼ S15 BT.
(Old BT)

A maple, 6" dia., bears S.13°W., 94 lks., mkd: ¼ S16 BT
(Old BT)

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland & John Powell - May 28, 1962 - C.S. File 52/121

Found - All orig. BTs except SW BT. We do not open.
Stone at corner as recorded. BTs show good scars.
Set brass cap alongside corner stone & mkd S 9|S 10 T29S R1W
S 16|S 15

New BTs- 15" R.Fir bears S.22°W., 15.0 ft. scribed S16 T29S R1W CS BT.

14" R.Fir bears N.62°E., 32.0 ft. scribed S10 T29S R1W CS BT.

continued next page

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 15 & 16 (North) only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82

Found - Orig. 10" D.Fir S.10°E., 18.5, shows good scar.
15" D.Fir, now down S.22°W., 15.0 ft. 1962
14" now 15" D.Fir N.62°E., 32.0 ft. pitched over
scribe visible. 1962
Co. Surv. brass cap mkd. in error in 1962 & stone at
sec. cor.

Remarked brass cap as follows: County Surveyors T29S R1W
Office S10
1962 S 16|S 15

New BT - 26" W.Fir S.70°W., 47.0 ft. mkd: T29S R1W S16 CS BT.
Note - This corner lies 128.7 East of sec. cor. to secs. 9
& 10 only.