

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6176)

Point for ¼ sec. cor. determined as hereafter set forth.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 9|S10
1922

from which

A fir, 24" dia., bears N.82°E., 27 lks., mkd: ¼ S10 BT.

A fir, 48" dia., bears S.29°W., 62 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland & John Powell - May 28, 1962 - C.S. File 52/121

Found - Brass cap at corner
Orig. 48" now 40" Fir snag S.29°W., 5.0 ft. not 40.9 ft., shows old axe work, no scribing found.
Orig. NE BT not found.

Note - This corner in old burn area & lies at top bank & on East side of Dupont Creek.

New BTs- 14" R.Fir bears S.19°E., 43.4 ft scribed ¼ S10 CS BT
4" R.Fir bears N.44°E., 10.5 ft. scribed ¼ S9 CS BT