

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6177)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T29S R1W  
S 4 | S 3  
S 9 | S 10

from which

- A fir, 8" dia., bears N.7°E., 24 lks., mkd: T29S R1W S3 BT
- A fir, 12" dia. bears S.45°E., 11 lks mkd: T29S R1W S10 BT
- A dogwood, 6" dia., bears S.23°W., 18 lks., mkd: T29S R1W S9 BT.
- A maple, 7" dia. bears N.32°W., 26 lks mkd: T29S R1W S4 BT