

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6178-9)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for
¼ sec. cor., with brass cap marked

¼
S 4 | S 3
1922

from which

A hemlock, 7" dia., bears S.19°E., 42 lks., mkd: ¼ S3 BT.

A hemlock, 10" dia., bears N.71°W., 17 lks., mkd: ¼ S4 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - June 19, 1985 - C.S. File 62/28-7

Found - 1922 GLO brass cap, on an IP protruding 10" above
ground, properly marked.

7" Hemlock, now 10" in dia., Pacific Yew with a
single partially healed blaze, scribing visible
"¼ S3 BT", bears S.19°E., 27.7 ft. (Orig)

10" Hemlock, now a stump hole, bears N.71°W., 11.2
ft. No evidence of tree found. (Orig)

New BTs- 6" dia., double trunked dogwood, double blazed &
scribed on east trunk "¼ S4 CS BT" bears S.47°W.,
10.4 ft. to root crown.

7" dia., W.Fir double blazed & scribed "¼ S3 CS BT"
bears N.13¼°E., 36.6 ft.

22" dia., W.Fir double blazed & scribed "¼ S3 CS BT"
bears N.84½°E., 37.6 ft.